

## :: Elastic Green

polyester fine putty - green

### CHARACTERISTICS

Elastic green is a 2K-polyester filler, developed specially for the body painter and fulfilling the highest demands on quality.

- High standard of quality
- Very fine surface
- Almost pore-free surface
- The optimum putty for the body painter
- For use on steel surfaces only
- Not for use on galvanised steel and aluminium surfaces

### APPLICATION

This very fine putty can be used for filling pores and repairing small scratches or surface defects.

### PRODUCT DATA

MATERIAL DATA:

- Delivery Viscosity at +20°: paste-like
- VOC content: 2004/42/IIB (b) (250)

### HANDLING

HANDLING:

The surface must be clean, dry and grease free.

**MIXING INSTRUCTIONS:**

No more than 2-3 % of hardener should be added to 100% by weight of polyester putty.

It is strongly recommended to avoid any overdosage of the hardener paste. It can cause perfusion and a change of colour of the topcoat.

**POT LIFE:**

3-4 minutes at room temperature of +20°C

**REACTION TEMPERATUR:**

At least +5°C

**APPLICATION:**

Apply with a spreader

**DRYING TIME:**

Air drying 15 – 20 minutes at room temperature of +20°C

**SANDING CHARACTERISTICS:**

After the indicated drying time

**As filling putty:**

First sanding – dry with P80 - P120

Re-sanding - dry with P120 - P 240

**As fine putty:**

First sanding – dry with P120 - P180

Re-sanding – dry with P180 - P240

**REWORKING:**

The fine putty can be reworked with CS Spray or filled with all 2K acrylic fillers available on the market.



10/2017

**STORAGE:**

Ca. 6 - 8 months at 18° - 20° C in closed original container

**SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Security Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE