

:: Master Tape Green

masking tape

CHARACTERISTICS

Master Tape Green is a slightly creped, flexible masking tape with excellent elongation characteristics and a high initial adhesion strength. This product is suitable for masking jobs for wet sanding as well as for solvent-based or water-based application of color paints with subsequent drying in a drying booth. It will adhere to painted metal, rubber, glass or chrome parts. After the drying, Master Tape comes off cleanly and leaves no residue.

APPLICATION

Professional-quality masking tape for reliable overspray protection during application processes with subsequent booth drying up to 110°C.

PRODUCT DATA

MATERIAL DATA:

(Average values)

Backing material: Special paper

Total thickness: 140 µm ± 10% (AFERA 5006)

Adhesive to steel plate (N / cm): > 2.3 (AFERA 5001)

MD Tensile strength (N /cm): > 34 (AFERA 5004)

MD Elongation at break: > 9 % (AFERA 5004)

Temperature resistance: 110 °C

stability in storage (23°C / 50% RH): 18 month

DIMENSION:

Standard roll length: 50 m

Widths: 19, 25, 30, 38, 50 mm



02/2018

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE