

:: Booth Mask

paint booth protection mask

CHARACTERISTICS

BOOTH MASK is a water based, sprayable masking that protects spray booth surfaces from paint overspray. The liquid material dries to a clear and tack free film protecting the surface from overspray and solvents. The protective film remains crystal clear for a long time and does not yellow. Therefore it does not affect the lighting conditions in the booth. After ca. 3 months or ca. 150 paint applications the film can be easily washed off with water.

BOOTH MASK is biodegradable.

APPLICATION

BOOTH MASK is used for protecting the booth against overspray. Booth walls and lamps can be sprayed and protected with BOOTH MASK. It is also suitable for protecting paint benches and other equipment from overspray and drips.

PRODUCT DATA

Material data:

Form: Liquid

Colour: Transparency

Smell: Uncharacteristically, slightly alcoholic

pH value: 4.5 - 5.5

Oxidising: No

Flashpoint: > 93°C

Specific gravity: 1.2 g / l (+20°C)

Packaging: Can

Contents: 5 or 20 litres

Use: 1 litre per 15 m²

HANDLING**Application:**

The walls of the booth should be clean, or newly painted, so as to ensure optimum lighting conditions. Ensure that all surfaces are completely dry. Apply a thick coat to the walls of the booth and the lights. After ca. 10 minutes apply a second coat to areas where there is a high degree of overspray. Avoid runs and drips. Allow BOOTH MASK to dry completely.

ATTENTION:

In case of newer cabins with bare aluminium door- and window frames adhesion problems may arise!

Tools:

BOOTH MASK should be applied with a spray gun suitable for water based materials. Recommended nozzle size: 2.2 mm, HVLP 1.9. Booth Temperature: approx.: 21°C

Removing / Cleaning:

Turn off all power to booth lamps and electrical outlets. BOOTH MASK can be removed in the following two ways:

1. From smooth walls BOOTH MASK can be peeled off as a film.
2. On rough surfaces such as concrete, stone or cement render it is recommended that BOOTH MASK is washed off with a pressure washer.

Ensure all surfaces are dry before re-applying BOOTH MASK.

Avoid overspray with water to walls that are already treated with BOOTH MASK.

For the protection of the booth floor as well as grills we recommend our product

DUST KEEPER.



10/2017

Efficiency: The coating should be renewed after ca. 3 months or 150 paint applications.

Otherwise it may be difficult to remove the BOOTH MASK film.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

Copyright VOSSCHEMIE