

## :: Fine Line Tape Blue

paint line tape

### CHARACTERISTICS

FINE LINE TAPE BLUE is a heat resistant film masking tape for the finest high quality paint edge lines. This product creates crisp, clean edges. The tape's extreme flexibility allows you to tape curves as well as long, straight lines. It will adhere to painted metal, rubber, glass or chrome parts. After the vehicle leaves the drying booth, FINE LINE TAPE BLUE comes off cleanly and leaves no residue.

### APPLICATION

High quality masking tape for multi colour paint jobs and the painting of special designs.

### PRODUCT DATA

#### MATERIAL DATA

Backing material: Poly vinyl chloride film  
 Total thickness: 0,13 mm  
 Colour: Blue  
 Adhesion to steel: 16,42 N/100 mm  
 Adhesion to steel (20min. dwell): 26,30 N/100 mm  
 Tensile Strength: 210 N/100 mm  
 Elongation at break: 100 %  
 Application area: 0°C → +155°C  
 Solvent resistance: Very good

#### DIMENSIONS

Standard roll length: 33 m  
 Widths: 3, 6, 9, 12, 19 mm

## **HANDLING**

The working temperature should be between +15°C and +30°C.

Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23°C.

## **PRECAUTIONS**

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C. Stored under these conditions shelf life will be a minimum of one year.

## **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.



02/2018

Copyright VOSSCHEMIE