

KS-250

Cavity protection

V05
05/2024

Description

- Cavity protection spray
- Wax like cavity protection
- Corrosion protection
- Melting point: 160 °C

Area of application

- Repairing and reworking existing preservations

Benefits

- Very high melting point
- Drip-free
- Rust protection
- Adhesion on metal

Application advice

Not overpaintable

Product Data

Packaging:	500 ml container
Color:	transparent
High melting point:	160°C
Specific gravity:	approx. 0.679 kg/l
Density at 20°C:	approx. 0.73 kg/l
Shelf life:	at least 5 years

Handling

Surface preparation:

The surfaces to be treated must be free of coarse rust and as dust-free as possible. Problem areas such as corners, edges and weld seams should be sprayed particularly carefully and thickly.

Application:

Shake container well before use and apply at room temperature (15°C to 30 °C).
Dust-dry after approx. 2 1/2 h, completely dry after approx. 3 1/2 h. The drying time depends on the ambient temperature, the air humidity and the applied layer thickness.



KS-250

Cavity protection

V05

05/2024



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE