

# MULTI PLUS

*Multifunctional polyester putty*

V06  
07/2024

## Description

- Multifunctional polyester putty
- Universal putty

## Area of application

- For filling small to deep imperfections, dents and scratches

## Benefits

- Good balance between being semi-solid and creamy
- Very easy to apply
- Multi adhesion

## Product Data

### Material data

Viscosity at 20°C: paste-like  
 VOC-content: 2004/42/IIIB (b) (250) < 250g/l  
 Colour: light grey

## Handling

### Surface:

- The substrate must be clean, dry and free of grease.
- Good adhesive properties on all roughly sanded bases.

### Mixing instructions

- Addition of 2-3 % of hardener.
- It is strongly recommended to avoid any over as well as underdosage of hardener. It can cause a lack of adherence and discolouration of the topcoat.

### Pot-life:

- At +20°C room temperature, 4-5 minutes.

### Reaction temperature:

- At least +10°C.

### Application:

Spread on with a spatula

### Hardening time:

- After the indicated drying time.

### Sanding:

- After the specified drying time.

### Reworking:

- The Multi Plus putty can be worked over with the following CS products: - Elastic weiss or Elastic beige and Spray

### Storage:

- Ca. 6 - 8 months at 18 - 20° C in closed original container

Steel	Aluminium	Galvanized tin	GRP	Plastic	2K Polyester putty	Wood
√	√	√	√	X	√	√



# MULTI PLUS

*Multifunctional polyester putty*

V06

07/2024



## Storage and transportation conditions

Allow the product to reach the recommended application temperature naturally (avoid rapidheating/ cooling). It is not recommended to apply the product at a temperature below 18 °C.

Low application temperature changes the coating's properties and may impair the visual.



## Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE