Silver Tape

fabric tape



V04 02/2025

Description

- Fabric tape
- Waterproof
- Temperature resistant up to 80 °C / 3 h

Area of application

- Usable for different masking work
- Sanding edge protection
- Support tape for glued parts

Benefits

- High adhesion on a multitude of surfaces
- Resistant to cold and heat

Product Data

Material data

Backing material: Cotton-polyester weave coated with LDPE

Dimensions: $50 \text{ m} \times 50 \text{ mm} \times 0,30 \text{ mm}$

Colour: silver

Tensile strength: 147 N / 25 mmAdhesive strength 6.9 N / 25 mm

Elongation: 12%

Heat and cold resistance: -15°C bis +60°C Max. heat resistance: 80 °C / 3 hours Shelf life at 10°C - 30°C: 24 Monate

Mesh: 70

Handling

Apply at temperatures between 0°C and 35°C. The surface must be clean and free of grease, oil, and dirt. Be very careful to avoid touching the adhesive; the tape will not adhere as well.

To achieve the best possible adhesive strength, exert maximum pressure when initially applying the tape. The maximum adhesive strength occurs at 23°C 24 hours after application.

Store in a clean, dry, and well-ventilated place. Store at temperatures of 10°C to 30°C. Under these conditions, we guarantee a shelf life of at least 6 months.



Silver Tape

fabric tape



V04 02/2025



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

© VOSSCHEMIE